

**Typical Properties**

|                             |                   |
|-----------------------------|-------------------|
| Appearance                  | Dark Brown Fluid. |
| Specific Gravity@60/60°F    | 0.970             |
| Density,lb/gal              | 8.07              |
| Viscosity@100°F(210°F),SUS  | 1775 (175)        |
| Viscosity@100°F(210°F),cSt  | 375 (35)          |
| Total Sulfur(Active),%wt    | 10.5 (0)          |
| Neutralization,meqKOH/g     | ≤ 8               |
| Flash Point C.O.C.,°F(°C)   | > 400 (> 204)     |
| Copper Corrosion+           | 1b                |
| Std Packaging (NW / GW, Kg) | 212.0 / 195.0     |

**Product Description**

**MAYCO BASE 1351** is a sulfurized fatty material, which due to its low viscosity lends itself to a variety of ferrous application needs.

**MAYCO BASE 1351** can also be used in severe operations on difficult to machine brass and bronzes due to its non-staining characteristic.

**MAYCO BASE 1351** can be used in dual-purpose applications and is an additive of choice in the formulation of way lubricants, where the recommended treat is 5% by weight.

| Applications                       | Suggested Treat Rates, %wt |
|------------------------------------|----------------------------|
| Waylube                            | 5                          |
| Tapping                            | 10 - 15                    |
| Cold Fordging                      | 25 - 50                    |
| Tapping / Automatic Screw Machines | 10 - 20                    |
| Turning                            | 5 - 10                     |

Print date: 13-09-25

**Disclaimer:** Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.