

Supplier - SMART OIL

FoamQuer 9936

Concentrate & Tankside Additive

High Performance Water-Based Defoamers

Typical Properties

Appearance	Translucent White To Light Yellow Liquid
Specific Gravity @ 25°C	1.000 - 1.100
Vis. @25°C, cp	80 - 400
Solid Content, %wt.	> 80
pH Value (50% Water Dilution)	7.0 - 8.5

Product Description

FOAMQUER 9936 is a compound of modified-siloxane emulsion containing highly concentrated components with optimal hydrophobic and hydrophilic balance; which accomodates the otherwise contradicting targets of the defoaming performance and system compatibility. The product is suitable for various industrial fluids such as cleaners, cutting fluids, and for the application in paint spray booths.

FOAMQUER 9936 has a strong dispersion performance to maintain a clear system, which specially suitable for synthetic.It can be used in soluble oils and semi-synthetic, and also with good performance in high-shear machining conditions.

FOAMQUER 9936 possesses low surface tension with high spreading coefficient; and appropriate droplets size to rupture foam cell lamellas; which results in fast foam collapses.

FOAMQUER 9936 is significantly cost-effective when compared to traditional PDMS-based or siloxane polyether-based defoamers. Apart from the fast foam knock-down characteristic, it possesses good washing property against the wetting defects of craters or fisheyes formation on the surface of the workpiece, so it is suitable for secondary processing like paint spray. By virtue of its unique molecular structure, the product is readily dispersible in water dilutable systems to maintain a clear system. It is not prone to self-agglomeration during usage and storage, so can ensure the passage in the system pipes.

FOAMQUER 9936 can also be used as tankside additive in water dilutable systems.

Recommended Starting Dosage Level

The recommended dosage range is 0.05 - 0.2% (500 - 2000ppm). However, the optimal dosage depends on system formulation. For tank-side addition, recommended starting dosage is 0.005% (50 ppm).

Storage and Use Condition

- Always mix thoroughly before use, as phase separation will occur after long storage time;
- Storage under normal temperature up to 60°C;
- Should be placed in closed container within shaded and ventilated area; do not expose to direct sunlight, and away from heat sources.

Print date: 13-06-26

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.