Supplier - SMART OIL FoamQuer 9775

Polyacrylate Copolymer

Typical Properties

Appearance S.G. @ 25°C Viscosity@25°C, cp Flash Point C.O.C.,°C Std Packaging (NW / GW, Kg)

Colorless Transparency Liquid 0.750 - 0.850 5.00 -8.00 > 80 177.0 / 160.0

Product Description

FOAMQUER 9775 is a polyacrylate copolymer based defoaming additive. It has good dispersibility in mineral oils, synthetic oils, and synthetic esters. It can effectively decrease the air solubility in the system and inhibit the bubble formation. The product has good air release functionality and defoaming characteristic, which is suitable for using in the formulations of gear, hydraulic, turbine and other industrial oils.

FOAMQUER 9775 contain no silicon and is blended with specially selected solvents that will neither get the lubricant hazy nor decrease the product lubricity.

FOAMQUER 9775 can be used by mixing with **FOAMQUER 9300** to strengthen the defoaming performance in the system.

FOAMQUER 9775 is 50- 1000 ppm.

Storage and Handling

- The product may have phase separation after prolonged storage, always mix thoroughly before use;
- Store at room temperature; not suitable for temperature higher than 60°C;
- Product should be stored in closed container and placed in sheltered and ventilated place. Keep away
 from direct sunlight and heat source.

Print date: 13-09-25