Supplier - SMART OIL
Smart Base 1219

Sulfurized Fatty Oil

## **Typical Properties**

Appearance	Dark Brown Liquid
Specific Gravity@25℃	1.000 - 1.100
Viscosity@40°C, cSt	550 - 850
Sulfur Content (Active), %wt	17 - 20 (6)
Acid Value, mgKOH/g	≤ 8
Flash Point C.O.C., °C	> 190
Copper Corrosion+	4B
$P_B / P_D$ , $kg++$	88 / 315
Std Packaging (NW / GW, Kg)	217.0 / 200.0

## **Product Description**

**SMART BASE 1219** is a sulfurized fatty oil additive with relatively high sulfur content. It possesses high lubricity, can exhibit superior performance in cold heading and drawing oil formulations.

**SMART BASE 1219** possesses superior EP properties, so it is specially suitable for machining tough metals like stainless steels and titanium alloys.

**SMART BASE 1219** contains active sulfur; so it is not suitable for processing copper, bronze and brass.

<u>Applications</u>	Suggested Treat Rates, %wt
Reaming	10 - 20
Reaming	10 - 20
Cold Heading (Cut Side Only)	20 - 30
Reaming	10 - 20
Turning	5 - 10

Print date: 13-09-25