Supplier - SMART OIL
Smart Base S2215C

Universal Emulsifier Package

## **Typical Properties**

Appearance	Amber Liquid
Specific Gravity@25°C	1.000 - 1.100
Viscosity@40°C, cSt	210 - 230
pH Value (5% Water Dilution)	8.0 - 9.5
Std Packaging (NW / GW, Kg)	222.0 / 205.0

## **Product Description**

**SMART BASE S2215C** is a universal emulsifier package. It not only possesses the elements for soluble oil needs, such as lubricity, EP and antirust, but also has mixed dosage of anti-microbial agents and fungicides; which ensure long usage life. It provides good working conditions and is highly cost-efficient.

**SMART BASE S2215C** provides superior lubricity and protects non-ferrous metals of copper and aluminium well.

**SMART BASE S2215C** exhibits strong antirust property, and is suitable for operations on ferrous metals such as cast irons, general steels and alloy steels. End users can use it as water-based rust preventive at 2% dilution ratio after blended to the soluble oils.

## Suggested treat rate:

15 - 33% SMART BASE S2215C in SN150 base oil; can blend to different grades of soluble oils.

<u>Applications</u>	Suggested Treat Rates, %wt
	Soft Stell / Alloy Steel / Copper / Aluminum Alloy
Boring & Threading	1:15 / 1:10 / 1:35 / 1:12
Turning, Milling, Drilling	1:25 / 1:20 / 1:35 / 1:15
Sawing	1:25 / 1:25 / 1:35 / 1:15
Grinding	1:40 / 1:40 / 1:40 / 1:40

Print date: 13-09-25