

Supplier - FUNCTIONAL

Paratac*Tackifiers**Tackifiers*

Typical Properties

Specific Gravity	0.880
Density,lbs/gal	7.3
Flash Point,°C(°F)	> 170 (338)
Kinematic Viscosity@100°C(60°C),cSt	2950 (10000)
Color(ASTM D1500)	< 3.0

Product Description

PARATAC is a tackifier used in various types of industrial oils to prevent dripping, spattering and wiping off. Main applications include: bar and chain (saw) oils; slide-way oils; open gear oils and greases; rock drill oils; anti- mist cutting oils; rust preventatives; wire-rope (cable) lubes; circulating oils; rail curve greases; textile machinery oils; commercial blasting agents; agriculture spray oils.

PARATAC is an oil solution of high molecular weight polyisobutylene.The diluent oil in PARATAC is lightcolored paraffinic oil.

Print date: 13-06-26

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.